

EFFE 3TI
PACKAGING TECHNOLOGIES

SPINNY S570

semi-automatic wrapping machine



MADE IN ITALY
SINCE 1999

Your Products, Our Care



SPINNY

MAIN FEATURES

- Standard model: wrapping of products on pallet with stretch film, having dimensions up to 1200 mm (L) X 1000 mm (W), with load capacity up to 2000 kg.
- Rotary table with diameter 1650 mm (standard), 1800 mm and 2000 mm
- Pallet wrapping with height from 2600 mm up to 3600 mm.
- Programmed to automatically perform reinforcement wraps at different heights.



TOUCH SCREEN



MOTORIZED PRE-STRETCH



IOT



ROPING

INDUSTRY 4.0 CERTIFIED WRAPPING MACHINE WITH MOTORIZED PRE-STRETCH, AUTOMATIC FILM TYING, CUTTING AND WELDING



Equipped with a touch screen panel with 10 customizable wrapping programs.

The machine has an IOT device that allows it to be controlled through a SecureCloud-based system (optional)



The **MOTORIZED PRE-STRETCH** system is a device that **reduces the amount of stretch film** used to wrap each pallet, maintaining excellent product stability (even for lightweight and unstable products, which would otherwise be impossible to wrap with traditional systems) and ensuring film elongation of **up to 300%** (1 m of film = 4 m of film applied to the pallet with 300% pre-stretch).

The stretch film is dispensed and pre-stretched at a constant tension via rollers, thanks to an electronic system that monitors the speed.

ROPING

Furthermore, on both pre-stretch systems, it is possible to reinforce the film laps on the pallet using the cord **reduction system**: this allows the film cross-section to be reduced, creating a real ultra-resistant "cord" that therefore guarantees **greater product stability**.

2-MOTORS PRE-STRETCH (OPTIONAL)

Based on the same concept as the single motor pre-stretch, the DUAL MOTOR version has been designed to guarantee even **greater savings**, up to a variable stretching of the stretch film that can reach **400%** (1m of film = 5m of film applied to the pallet with 300% pre-stretch).



S570

semi-automatic wrapping machine

ONE STEP BEYOND WITH THE BEST OPTIONALS

DATALOGGER.2 (OPTIONAL)



A system designed and developed by EFFE3ti srl to collect real-time data from machines on a cloud platform with a state-of-the-art control panel. This data is then collected, processed, and shared to monitor production, performance, consumption, and machine status, and generate statistics.

THE VALUE OF INFORMATION

Monitor the activity of your installed machines, identify any issues, plan maintenance, and, thanks to direct control of stretch film consumption, you can implement business opportunities such as supplying wrapping machines on a "pay per pallet" basis.



productivity
monitoring



consumption
monitoring



improving
efficiency



improving
production
processes



report and
analysis

(OPTIONAL)

CORVINA

Advanced smart manufacturing and smart machines solutions platform that enable real-time monitoring, predictive maintenance, and remote control capabilities.

VOLUMETRIC SENSING SYSTEM

A camera positioned on the top of the machine detects the volume of the product.

PHOTOGRAPHIC SYSTEM

It can take up to 4 photos (one for each side of the pallet) before and after the wrapping process, useful for refuting claims related to missing or damaged goods during transport.

WEIGHING SYSTEM

A scale under the turntable detects the weight of the product.

TOUCHSCREEN DASHBOARD

A second touch screen monitor to display all information on the packaging processes and real-time information.

REMOTE COMMAND

To select the wrapping program and start the cycle remotely.



SPINNY S570 is a pallet wrapping machine that immediately improves the efficiency of your company's logistics **by eliminating the annoying, time-consuming and often dangerous manual winding operations.**

With Datalogger.2 (optional) you can monitor the machine even remotely, program the wrapping cycles and produce statistics on consumption and work cycles.

At EFFE3ti, we care deeply about innovation and are committed to continuous product development. Safety is a priority, so all SPINNY models comply with the applicable Machinery Directive: a guarantee of production in compliance with health, safety, and environmental requirements.

TECHNICAL CHARACTERISTICS

- Pre-stretch ratio up to 300%; standard 200%
- Automatic pallet height detection via photocell
- Separate programming of high and low reinforcement turns
- Table rotation adjustable from 5 to 15 rpm
- Table stop position controlled by sensor
- Adjustable reel carriage speed
- Reel carriage fall prevention system
- PLC-controlled work cycles with HMI 7"
- Automatic film binding, cutting, and sealing system
- IP55 protection

POWER SUPPLY


- Tension: 230 V single phase
On demand, 400-415 V triple phase $\pm 10\%$
- Frequency: 50 Hz
- Installed power: 3 kW
- Auxiliary power supply: 24 V DC

PNEUMATIC SYSTEM

- Compressed air: required pressure 5 bar
- 180 nl/cycle

FILM (LLDPE) AND REEL CHARACTERISTICS

- Thickness: $12 \div 23 \mu\text{m}$
- Suggested thickness: $20 \mu\text{m}$
- Internal diameter: 76 mm
- Height: 500 mm
- Maximum weight: 20 kg
- Maximum diameter: 250 mm



SPINNY S570
semi-automatic wrapping machine

R2602

follow us



www.effe3ti.com

EFFE3ti srl | C.so Garibaldi 298 | 13045 GATTINARA (VC) ITALY | +39 0163 828911

